

PRODUCT-DETAILS

# A9-30-10 110-120V60HZ

## A9-30-10 110-120V60HZ Contactor



### General Information

Extended Product Type	A9-30-10 110-120V60HZ
Product ID	1SBL141001W8410
EAN	3471522031846
Catalog Description	A9-30-10 110-120V60HZ Contactor

#### Long Description

A 9 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

### Ordering

Minimum Order Quantity	160 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SBL131001R8410

### Popular Downloads

Instructions and Manuals	FPTC407721P0001
--------------------------	-----------------

---

**Dimensions**


---

Product Net Width	44 mm
Product Net Depth / Length	74 mm
Product Net Height	74 mm
Product Net Weight	0.34 kg

---



---

**Technical**


---

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Rated Operational Current AC-1 ( $I_e$ )	(690 V) 40 °C 25 (690 V) 55 °C 22 (690 V) 70 °C 18
Rated Operational Current AC-3 ( $I_e$ )	(415 V) 55 °C 9 A (440 V) 55 °C 9 A (500 V) 55 °C 9 A (690 V) 55 °C 7 A (380 / 400 V) 55 °C 9 A (220 / 230 / 240 V) 55 °C 9
Rated Operational Power AC-3 ( $P_e$ )	(415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 2.5 kW (220 / 230 / 240 V) 2.2 kW
Rated Operational Current AC-15 ( $I_e$ )	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 90 A
Rated Control Circuit Voltage ( $U_c$ )	50 Hz 110 V 60 Hz 110 ... 120 V
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Terminal Type	Screw Terminals

---



---

**Technical UL/CSA**


---

General Use Rating UL/CSA	(600 V AC) 21 A
---------------------------	-----------------

---



---

**Environmental**


---

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 55 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
RoHS Status	Following EU Directive 2011/65/EU

---



---

**Certificates and Declarations (Document Number)**


---

CB Certificate	CB_CN44759
CCC Certificate	CCC_2018010304059156
CQC Certificate	CQC2013010304615753 CQC2018010304059156 CQC2004010309130463
CSA Certificate	CSA_1041746
Declaration of Conformity - CCC	2020980304001607 2020980304001616 2020980304001229
Declaration of Conformity - CE	1SBD250801U1000
EAC Certificate	EAC_RU C-FR ME77 B03599
Instructions and Manuals	FPTC407721P0001
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250801U1000
UL Certificate	UL_20160205-E312527-10-2
UL Listing Card	UL_E312527

## Container Information

Package Level 1 Units	box 160 piece
Package Level 1 Width	78 mm
Package Level 1 Depth / Length	76.5 mm
Package Level 1 Height	46.5 mm
Package Level 1 Gross Weight	54.4 kg
Package Level 1 EAN	3471522031846
Package Level 2 Units	160 piece
Package Level 2 Gross Weight	54.4 kg
Package Level 3 Units	480 piece

## Classifications

Object Classification Code	Q
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

