

PRODUCT-DETAILS

A9-22-00 230-240V 50Hz / 240-260V 60Hz

A9-22-00 230-240V 50Hz / 240-260V 60Hz

Contactors



General Information

Extended Product Type	A9-22-00 230-240V 50Hz / 240-260V 60Hz
Product ID	1SBL141501R8800
EAN	3471522033888
Catalog Description	A9-22-00 230-240V 50Hz / 240-260V 60Hz Contactor
Long Description	A 9 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 2 N.O. + 2 N.C. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SBL131501R8800

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch02
Instructions and Manuals	FPTC407721P0001

Dimensions

Product Net Width	44 mm
Product Net Depth / Length	74 mm
Product Net Height	74 mm
Product Net Weight	0.34 kg

Technical

Number of Main Contacts NO	2
Number of Main Contacts NC	2
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Standards	Devices complying with international standards IEC 947-1 / 947-4-1, and European standards EN 60 947-1 / 60 947-4-1. Electromagnetic compatibility (EMC) acc. to amendment A11 to IEC 947-1, EN 60 947-1 and amendment 2 to IEC 947-4-1
Rated Operational Voltage	Main Circuit 690 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 26 A
Rated Operational Current AC-1 (I_e)	(690 V) 40°C 25 (690 V) 55°C 22 (690 V) 70°C 18
Rated Operational Current AC-3 (I_e)	(220 / 230 / 240 V) 55°C 9 A (380 / 400 V) 55°C 9 A (415 V) 55°C 9 A (440 V) 55°C 9 A (500 V) 55°C 9 A (690 V) 55°C 7 A
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 25 A
Maximum Breaking Capacity	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 250 A $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 90 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 230 ... 240 V 60 Hz 240 ... 260 V
Coil Consumption	Average Holding Value 50 / 60 Hz 8 V-A Average Pull-in Value 50 Hz 74 V-A Average Pull-in Value 60 Hz 70 V-A Holding at Max. Rated Control Circuit Voltage 50 Hz 8 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 8 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 2 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 70 V-A

	Pull-in at Max. Rated Control Circuit Voltage 60 Hz 80 V-A
Operate Time	Between Coil De-energization and NC Contact Closing 9 ... 16 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NC Contact Opening 7 ... 21 ms Between Coil Energization and NO Contact Closing 10 ... 26 ms
Connecting Capacity Main Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 21 A
------------------------------	-----------------

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... 55 °C Near Contactor for Operation in Free Air (Uc) -40 ... 70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

BV Certificate	BV_2634H07559E0
CB Certificate	CB_CN44759
CCC Certificate	CCC_2018010304059156 CCC_2004010309130463
CQC Certificate	CQC2013010304615753 CQC2018010304059156 CQC2004010309130463
CSA Certificate	CSA_1041746
Declaration of Conformity - CCC	2020980304001607 2020980304001616 2020980304001229
Declaration of Conformity - CE	1SBD250802U1000
DNV Certificate	DNV-GL_TAE00000TX
DNV GL Certificate	DNV-GL_TAE00000TX
EAC Certificate	EAC_RU C-FR ME77 B03599
Environmental Information	1SBD250001E1004
Instructions and Manuals	FPTC407721P0001
LR Certificate	LRS_9830011E4
RINA Certificate	RINA_ELE172319XG001
RMRS Certificate	RMRS_0507015250

RoHS Information	1SBD250802U1000
UL Certificate	UL_20160205-E312527-10-2
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	78 mm
Package Level 1 Depth / Length	76 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.34 kg
Package Level 1 EAN	3471522033888
Package Level 2 Units	box 63 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	21.42 kg
Package Level 3 Units	1220 piece

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

