

PRODUCT-DETAILS

AL12-30-10RT 24V DC

AL12-30-10RT 24V DC Contactor



General Information

Extended Product Type	AL12-30-10RT 24V DC
Product ID	1SBL163010R8110
EAN	3471522360410
Catalog Description	AL12-30-10RT 24V DC Contactor

Long Description

AL12 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The AL...RT contactors are the Ring Tongue terminal version of the AL... range. The AL... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with solid core magnet circuit. The polarity on the coil terminals (A1+ and A2-) must be respected - Accessories: a wide range of accessories is available. AL... contactors are fitted with low consumption DC coils and are suitable for a direct control by PLC outputs.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC104032D0201
Instructions and Manuals	1SBC101006M5501

Dimension Diagram

FPTE307902

Dimensions

Product Net Width	44 mm
Product Net Depth / Length	97 mm
Product Net Height	78 mm
Product Net Weight	0.52 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ }^{\circ}\text{C}$ 28 A acc. to IEC 60947-5-1, $q = 40\text{ }^{\circ}\text{C}$ 16 A
Rated Operational Current AC-1 (I_e)	(690 V) $40\text{ }^{\circ}\text{C}$ 27 (690 V) $55\text{ }^{\circ}\text{C}$ 25 (690 V) $70\text{ }^{\circ}\text{C}$ 20
Rated Operational Current AC-3 (I_e)	(415 V) $55\text{ }^{\circ}\text{C}$ 12 A (440 V) $55\text{ }^{\circ}\text{C}$ 12 A (500 V) $55\text{ }^{\circ}\text{C}$ 12 A (690 V) $55\text{ }^{\circ}\text{C}$ 9 A (380 / 400 V) $55\text{ }^{\circ}\text{C}$ 12 A (220 / 230 / 240 V) $55\text{ }^{\circ}\text{C}$ 12
Rated Operational Power AC-3 (P_e)	(415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 32 A
Maximum Breaking Capacity	$\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 440 V 250 A $\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100\text{ A}$) at 690 V 100 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour
Rated Operational Current DC-13 (I_e)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 2 / 144 A (125 V) 1.1 / 138 A (250 V) 0.55 / 138 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V

Rated Impulse Withstand Voltage (U_{imp})	6 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	DC Operation 24 V
Coil Consumption	Average Holding Value, from Warm State 3 W Average Pull-in Value, from Cold State 3 W
Operate Time	Between Coil De-energization and NO Contact Opening 10 ... 17 ms Between Coil Energization and NO Contact Closing 50 ... 100 ms
Connecting Capacity Main Circuit	Flexible with Cable Lug 0.75 ... 2.5 mm ² Rigid Cable 0.75 ... 2.5 mm ²
Connecting Capacity Auxiliary Circuit	Rigid or Flexible with Cable Lug 0.75 ... 2.5 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M 3.5 (+,-) pozidriv 2 screw with conic washer
Terminal Type	Ring-Tongue Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 25 A
---------------------------	-----------------

Environmental

Ambient Air Temperature	Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U_c) -40 ... 55 °C Close to Contactor without Thermal O/L Relay (U_c) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: A 20 g Closed, Shock Direction: B1 15 g Closed, Shock Direction: C1 20 g Closed, Shock Direction: C2 14 g Open, Shock Direction: A 10 g Open, Shock Direction: B1 5 g Open, Shock Direction: C1 8 g Open, Shock Direction: C2 8 g Shock Direction: B2 10 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CQC Certificate	CQC2012010304534830
CSA Certificate	CSA_1041746
Declaration of Conformity - CCC	2020980304001613
Declaration of Conformity - CE	1SBD250804U1000
Environmental Information	1SBD250121E1004
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101006M5501
RoHS Information	1SBD250806U1000

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	86 mm
Package Level 1 Depth / Length	141 mm
Package Level 1 Height	51 mm
Package Level 1 Gross Weight	0.52 kg
Package Level 1 EAN	3471522360410
Package Level 2 Units	box 28 piece
Package Level 2 Gross Weight	14.56 kg
Package Level 3 Units	336 piece

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

