

PRODUCT-DETAILS

A26-30-10 220-230V 50Hz / 230-240V 60Hz

A26-30-10 220-230V 50Hz / 230-240V 60Hz

Contactor



General Information

Extended Product Type	A26-30-10 220-230V 50Hz / 230-240V 60Hz
Product ID	1SBL241001T8010
EAN	3471522067807
Catalog Description	A26-30-10 220-230V 50Hz / 230-240V 60Hz Contactor
Long Description	A26 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SBL231001R8000

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch02
Instructions and Manuals	FPTC407722P0001

Dimensions

Product Net Width	54 mm
Product Net Depth / Length	93.6 mm
Product Net Height	90 mm
Product Net Weight	0.6 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 45 A acc. to IEC 60947-5-1, q = 40 °C 16 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 45 (690 V) 55 °C 40 (690 V) 70 °C 32
Rated Operational Current AC-3 (I _e)	(415 V) 55 °C 26 A (440 V) 55 °C 26 A (500 V) 55 °C 22 A (690 V) 55 °C 17 A (380 / 400 V) 55 °C 26 A (220 / 230 / 240 V) 55 °C 26
Rated Operational Power AC-3 (P _e)	(415 V) 11 kW (440 V) 15 kW (500 V) 15 kW (690 V) 15 kW (380 / 400 V) 11 kW (220 / 230 / 240 V) 6.5 kW
Rated Operational Power AC-6b (P _e)	(230 / 240 V) 40 °C, 50 / 60 Hz 11.5 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 11.5 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 9 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 19 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 15 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 19 kvar (440 V) 40 °C, 50 / 60 Hz 20 kvar (440 V) 55 °C, 50 / 60 Hz 20 kvar (440 V) 70 °C, 50 / 60 Hz 16.5 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 23 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 23 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 19 kvar (690 V) 40 °C, 50 / 60 Hz 32 kvar (690 V) 55 °C, 50 / 60 Hz 32 kvar (690 V) 70 °C, 50 / 60 Hz 26 kvar
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I _e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I _e AC-3
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 50 A

Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 420 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 170 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour
Rated Operational Current DC-13 (Ie)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 2 / 144 A (125 V) 1.1 / 138 A (250 V) 0.55 / 138 A
Rated Insulation Voltage (Ui)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (Uimp)	8 kV
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (Uc)	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
Coil Consumption	Average Holding Value 50 / 60 Hz 12 V·A Average Pull-in Value 50 Hz 125 V·A Average Pull-in Value 60 Hz 120 V·A
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 21 ms
Connecting Capacity Main Circuit	Flexible with Cable End 0.75 ... 4 mm ² Rigid Cable 1.5 ... 6 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 4 (+,-) pozidriv 2 screws with cable clamp
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 40 A
---------------------------	-----------------

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 55 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 55 °C Close to Contactor without Thermal O/L Relay (Uc) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

BV Certificate	BV_2634H07559E0
CB Certificate	CB_FR_602227A
CCC Certificate	CCC_2013010304615752

CQC Certificate	CQC2013010304615752 CQC2004010309133982
CSA Certificate	CSA_1033838_LR056745
Declaration of Conformity - CCC	2020980304001609 2020980304001227
Declaration of Conformity - CE	1SBD250801U1000
DNV Certificate	DNV-GL_TAE00000TX
DNV GL Certificate	DNV-GL_TAE00000TX
EAC Certificate	EAC_RU C-FR ME77 B03599
Environmental Information	1SBD250004E1003
Instructions and Manuals	FPTC407722P0001
LOVAG Certificate	LOVAG_FR97043
LR Certificate	LRS_9830011E4
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250801U1000
UL Certificate	UL_071301E39231

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	185 mm
Package Level 1 Depth / Length	302 mm
Package Level 1 Height	117 mm
Package Level 1 Gross Weight	6 kg
Package Level 1 EAN	3471522067807
Package Level 2 Units	box 10 piece
Package Level 2 Gross Weight	6 kg

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

