

PRODUCT-DETAILS

# A26-30-10 STIEBEL 220-230V50HZ

## A26-30-10 STIEBEL 220-230V50HZ Contactor



### General Information

Extended Product Type	A26-30-10 STIEBEL 220-230V50HZ
Product ID	1SBL241068R8010
EAN	3471523000414
Catalog Description	A26-30-10 STIEBEL 220-230V50HZ Contactor
Long Description	A26-30-10 STIEBEL 220-230V50HZ Contac

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

### Dimensions

Product Net Width	54 mm
Product Net Depth / Length	93.6 mm
Product Net Height	90 mm
Product Net Weight	0.6 kg

### Technical

Number of Main Contacts NO	3
----------------------------	---

Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 45 (690 V) 55 °C 40 (690 V) 70 °C 32
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 55 °C 26 A (440 V) 55 °C 26 A (500 V) 55 °C 22 A (690 V) 55 °C 17 A (380 / 400 V) 55 °C 26 A (220 / 230 / 240 V) 55 °C 26
Rated Operational Power AC-3 (P <sub>e</sub> )	(415 V) 15 kW (440 V) 15 kW (500 V) 15 kW (380 / 400 V) 11 kW (220 / 230 / 240 V) 6.5 kW
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 420 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 170 A
Rated Control Circuit Voltage (U <sub>c</sub> )	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Terminal Type	Screw Terminals

## Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 40 A
---------------------------	-----------------

## Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C
RoHS Status	Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

CQC Certificate	CQC2013010304615752 CQC2004010309133982
Declaration of Conformity - CCC	2020980304001609 2020980304001227
Declaration of Conformity - CE	1SBD250801U1000
EAC Certificate	EAC_RU C-FR ME77 B03599
RoHS Information	1SBD250801U1000

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	101 mm
Package Level 1 Depth / Length	115 mm
Package Level 1 Height	61 mm
Package Level 1 Gross Weight	0.6 kg
Package Level 1 EAN	3471523000414

Package Level 2 Units	box 24 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	14.4 kg
Package Level 3 Units	576 piece

---

## Classifications

---

Object Classification Code	Q
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003

---

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

