

PRODUCT-DETAILS

A30-30-10 110-115V 50Hz / 115-127V 60Hz

A30-30-10 110-115V 50Hz / 115-127V 60Hz

Contactors



General Information

Extended Product Type	A30-30-10 110-115V 50Hz / 115-127V 60Hz
Product ID	1SBL281001R8910
EAN	3471522071897
Catalog Description	A30-30-10 110-115V 50Hz / 115-127V 60Hz Contactor

Long Description	A30 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.
------------------	--

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch02
Instructions and Manuals	FPTC407722P0001

Dimensions

Product Net Width	54 mm
Product Net Depth / Length	108.3 mm
Product Net Height	90 mm
Product Net Weight	0.71 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Standards	Devices complying with international standards IEC 947-1 / 947-4-1, and European standards EN 60 947-1 / 60 947-4-1. Electromagnetic compatibility (EMC) acc. to amendment A11 to IEC 947-1, EN 60 947-1 and amendment 2 to IEC 947-4-1
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 65 A acc. to IEC 60947-5-1, q = 40 °C 16 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 55 (690 V) 55 °C 55 (690 V) 70 °C 39
Rated Operational Current AC-3 (I _e)	(415 V) 55 °C 32 A (440 V) 55 °C 32 A (500 V) 55 °C 28 A (690 V) 55 °C 21 A (380 / 400 V) 55 °C 32 A (220 / 230 / 240 V) 55 °C 33
Rated Operational Power AC-3 (P _e)	(415 V) 15 kW (440 V) 18.5 kW (500 V) 18.5 kW (690 V) 18.5 kW (380 / 400 V) 15 kW (220 / 230 / 240 V) 9 kW
Rated Operational Power AC-6b (P _e)	(230 / 240 V) 40 °C, 50 / 60 Hz 13 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 13 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 11 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 22 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 18.5 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 22 kvar (440 V) 40 °C, 50 / 60 Hz 24 kvar (440 V) 55 °C, 50 / 60 Hz 24 kvar (440 V) 70 °C, 50 / 60 Hz 20.5 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 28 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 28 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 23 kvar (690 V) 40 °C, 50 / 60 Hz 38 kvar (690 V) 55 °C, 50 / 60 Hz 38 kvar (690 V) 70 °C, 50 / 60 Hz 32 kvar
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I _e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I _e AC-3
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A

Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 63 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 820 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 340 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour
Rated Operational Current DC-13 (I _e)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 2 / 144 A (125 V) 1.1 / 138 A (250 V) 0.55 / 138 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 110 ... 115 V 60 Hz 115 ... 127 V
Coil Consumption	Average Holding Value 50 / 60 Hz 12 V-A Average Pull-in Value 50 Hz 125 V-A Average Pull-in Value 60 Hz 120 V-A
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 21 ms
Connecting Capacity Main Circuit	Flexible with Cable End 2.5 ... 10 mm ² Rigid Cable 2.5 ... 16 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 5 (+,-) pozidriv 2 screw with 2x (5.6x6.5 mm) connector
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 50 A
---------------------------	-----------------

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 55 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U _c) -40 ... 55 °C Close to Contactor without Thermal O/L Relay (U _c) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

BV Certificate	BV_2634H07559E0
CB Certificate	CB_FR_602227A
CCC Certificate	CCC_20130103046157
CQC Certificate	CQC20130103046157 CQC2004010
CSA Certificate	CSA_103
Declaration of Conformity - CCC	
Declaration of Conformity - CE	
DNV Certificate	
DNV GL Certificate	
EAC Certificate	
Environmental Information	
Instructions and Manuals	
LOVAG Certificate	
LR Certificate	
RINA Certificate	
RMRS Certificate	
RoHS Information	
UL Certificate	

Container Information

Package Level 1 Height	ck rt Level 1 Height	61 mm
Package Level 2 Height		
Package Level 3 Height		
Package Level 4 Height		

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

