

PRODUCT-DETAILS

A45-40-00 400-415V 50Hz / 415-440V 60Hz A45-40-00 400-415V 50Hz / 415-440V 60Hz Contactor



General Information

Extended Product Type	A45-40-00 400-415V 50Hz / 415-440V 60Hz
Product ID	1SBL331201R8600
EAN	3471522079862
Catalog Description	A45-40-00 400-415V 50Hz / 415-440V 60Hz Contactor
Long Description	A45 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch02
Instructions and Manuals	FPTC407701P0003

Dimensions

Product Net Width	92 mm
Product Net Depth / Length	119.5 mm
Product Net Height	110 mm
Product Net Weight	1.39 kg

Technical

Number of Main Contacts NO	4
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Standards	Devices complying with international standards IEC 947-1 / 947-4-1, and European standards EN 60 947-1 / 60 947-4-1. Electromagnetic compatibility (EMC) acc. to amendment A11 to IEC 947-1, EN 60 947-1 and amendment 2 to IEC 947-4-1
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 100 A
Rated Operational Current AC-1 (I_e)	(690 V) 40°C 70 (690 V) 55°C 60 (690 V) 70°C 50
Rated Operational Current AC-3 (I_e)	(415 V) 55°C 37 A (440 V) 55°C 37 A (500 V) 55°C 33 A (690 V) 55°C 25 A (380 / 400 V) 55°C 37 A (220 / 230 / 240 V) 55°C 40
Rated Operational Power AC-3 (P_e)	(415 V) 25 kW (440 V) 25 kW (500 V) 30 kW (690 V) 30 kW (380 / 400 V) 22 kW (220 / 230 / 240 V) 15 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 80 A
Maximum Breaking Capacity	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 900 A $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 490 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 600 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	50 Hz 400 ... 415 V 60 Hz 415 ... 440 V
Coil Consumption	Average Holding Value 50 / 60 Hz 18 V·A Average Pull-in Value 50 Hz 190 V·A

	Average Pull-in Value 60 Hz 180 V-A Holding at Max. Rated Control Circuit Voltage 50 Hz 18 V-A Holding at Max. Rated Control Circuit Voltage 50 Hz 5.5 W Holding at Max. Rated Control Circuit Voltage 60 Hz 18 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 5.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 180 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 210 V-A
Operate Time	Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 27 ms
Connecting Capacity Main Circuit	Flexible with Cable End 6 ... 16 mm ² Rigid Cable 6 ... 25 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 80 A
------------------------------	-----------------

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... 55 °C Near Contactor for Operation in Free Air (Uc) -40 ... 70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

BV Certificate	BV_2634H07559E0
CB Certificate	CB_CN45324
CCC Certificate	CCC_2018010304129267
CQC Certificate	CQC2018010304129267
CSA Certificate	CSA_1033838_LR056745
Declaration of Conformity - CCC	2020980304001622
Declaration of Conformity - CE	1SBD250802U1000
EAC Certificate	EAC_RU C-FR ME77 B03599
Environmental Information	1SBD250007E1003
Instructions and Manuals	FPTC407701P0003
LR Certificate	LRS_9830011E4
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250802U1000
UL Certificate	UL_20120830-E312527-10-1
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	142 mm
Package Level 1 Depth / Length	190 mm
Package Level 1 Height	136 mm
Package Level 1 Gross Weight	1.39 kg
Package Level 1 EAN	3471522079862
Package Level 2 Units	box 8 piece
Package Level 2 Gross Weight	11.12 kg

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

