

PRODUCT-DETAILS

AF75-22-00RT 48-130V50/60Hz/DC AF75-22-00RT 48-130V50/60Hz/DC Contactor



General Information	
Extended Product Type	AF75-22-00RT 48-130V50/60Hz/DC
Product ID	1SBL417510R6900
EAN	3471522245991
Catalog Description	AF75-22-00RT 48-130V50/60Hz/DC Contactor
Long Description	AF75 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting The AF contactors are fitted with an electronic coil interface which accepts a wide control voltage range, on AC 50/60 Hz or DC supplies. The same contactor can accept various supply voltages according to the different countries where the electrical equipment will be installed, or some fluctuation in the control voltage due to the local supply or network. The AF contactors are also fully suitable for operation in AC or DC control circuit liable to voltage interruptions or voltage dip risks. Advantages: - Wide voltage range, e.g. 100 250 V AC and DC - Can manage large voltage variations - Reduced power consumption - Very distinct closing and opening - Noise free - Can withstand voltage interruptions or voltage dip is Afr series 4-pole contactors are of the block type design Main poles and auxiliary contact blocks: 2 N.O. + 2 N.C. main poles, front and side mounted add-on auxiliary contact blocks - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

FPTC407767P00)02
---------------	-----

Dimensions	
Product Net Width	92 mm
Product Net Depth / Length	119.5 mm
Product Net Height	110 mm
Product Net Weight	1.5 kg

Technical	
Number of Main Contacts NO	2
Number of Main Contacts NC	2
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 508, CSA C22-2 N°14, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011 (on request), IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives.
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 125 (690 V) 55 °C 105 (690 V) 70 °C 85
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for le > 100 A) at 440 V 1300 A cos phi=0.45 (cos phi=0.35 for le > 100 A) at 690 V 630 A
Rated Control Circuit Voltage (U _c)	50 Hz 48 130 V 60 Hz 48 130 V DC Operation 48 130 V
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Terminal Type	Ring-Tongue Terminals

Technical UL/CSA	
General Use Rating UL/CSA	(600 V AC) 105 A

Environmental	
Ambient Air Temperature	Close to Contactor for Storage -60 +80 °C Near Contactor for Operation in Free Air (Uc) -40 70 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
RoHS Status	Following EU Directive 2011/65/EU
Certificates and Declarations (Document Number)	
CCC Certificate	CCC_2018010304134049
CQC Certificate	CQC2018010304134049

CQC2018010304134049 CQC2010010304402983

2020980304001624 2020980304001225 1SBD250803U1000

Declaration of Conformity - CCC

AF75-22-00RT 48-130V50/60Hz/DC

Instructions and Manuals	FPTC407767P0002
RoHS Information	1SBD250803U1000

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	142 mm
Package Level 1 Depth / Length	190 mm
Package Level 1 Height	136 mm
Package Level 1 Gross Weight	1.5 kg
Package Level 1 EAN	3471522245991

Classifications	
Object Classification Code	Q
ETIM 4	EC000196 - Contactor relay
ETIM 5	EC000196 - Contactor relay
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003

Categories

Low Voltage Products and Systems \rightarrow Control Products \rightarrow Contactors \rightarrow Block Contactors

