

PRODUCT-DETAILS

AE75-30-00RT 24V DC

AE75-30-00RT 24V DC Contactor



General Information

Extended Product Type	AE75-30-00RT 24V DC
Product ID	1SBL419010R8100
EAN	3471522244413
Catalog Description	AE75-30-00RT 24V DC Contactor

Long Description	<p>AE75 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The AE..RT contactors are the Ring Tongue terminal version of the AE... range. The AE... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with standard double-winding DC coils (with add-on factory-mounted lagging contact for insertion of the "holding" winding) - Accessories: a wide range of accessories is available.</p>
------------------	---

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC101018D0202
Instructions and Manuals	FPTC407767P0002

Dimensions

Product Net Width	82 mm
Product Net Depth / Length	108 mm
Product Net Height	110 mm
Product Net Weight	1.2 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40\text{ }^{\circ}\text{C}$ 125 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 $^{\circ}\text{C}$ 125 (690 V) 55 $^{\circ}\text{C}$ 105 (690 V) 70 $^{\circ}\text{C}$ 85
Rated Operational Current AC-3 (I_e)	(415 V) 55 $^{\circ}\text{C}$ 72 A (440 V) 55 $^{\circ}\text{C}$ 70 A (500 V) 55 $^{\circ}\text{C}$ 65 A (690 V) 55 $^{\circ}\text{C}$ 46 A (1000 V) 55 $^{\circ}\text{C}$ 28 A (380 / 400 V) 55 $^{\circ}\text{C}$ 75 A (220 / 230 / 240 V) 55 $^{\circ}\text{C}$ 75
Rated Operational Power AC-3 (P_e)	(415 V) 40 kW (440 V) 40 kW (500 V) 45 kW (690 V) 40 kW (380 / 400 V) 37 kW (220 / 230 / 240 V) 22 kW
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Maximum Breaking Capacity	$\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100$ A) at 440 V 1300 A $\cos\phi=0.45$ ($\cos\phi=0.35$ for $I_e > 100$ A) at 690 V 630 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U_c)	DC Operation 24 V
Coil Consumption	Average Holding Value, from Warm State 4 W Average Pull-in Value, from Cold State 200 W Pull-in at Max. Rated Control Circuit Voltage DC 200 W
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP10 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Terminal Type	Ring-Tongue Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 105 A
---------------------------	------------------

Environmental

Ambient Air Temperature	Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 55 °C Close to Contactor without Thermal O/L Relay (Uc) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

ASEFA Certificate	ASEFA_03101
CB Certificate	CB_FR_701506-A1
CQC Certificate	CQC2018010304129269
CSA Certificate	CSA_1033838_LR056745
Declaration of Conformity - CCC	2020980304001621
Declaration of Conformity - CE	1SBD250806U1000
Environmental Information	1SBD250019E1003
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407767P0002
LR Certificate	LRS_9830011
RINA Certificate	RINA_ELE1007979
RoHS Information	1SBD250806U1000
UL Certificate	UL_071301E39231

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	140 mm
Package Level 1 Depth / Length	146 mm
Package Level 1 Height	96 mm
Package Level 1 Gross Weight	1.2 kg
Package Level 1 EAN	3471522244413
Package Level 2 Units	box 20 piece
Package Level 2 Gross Weight	24 kg

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

