

PRODUCT-DETAILS

# A210-30-22 220-230V 50Hz

## A210-30-22 220-230V 50Hz Contactor



### General Information

Extended Product Type	A210-30-22 220-230V 50Hz
Product ID	1SFL511001R9102
EAN	7320500362372
Catalog Description	A210-30-22 220-230V 50Hz Contactor
Long Description	A210-30-22 220-230V 50Hz Contactor

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

### Popular Downloads

Instructions and Manuals	N/A
--------------------------	-----

### Dimensions

Product Net Width	140 mm
Product Net Depth / Length	180.5 mm
Product Net Height	227 mm
Product Net Weight	5.4 kg

---

**Technical**


---

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Rated Operational Current AC-1 ( $I_e$ )	(690 V) 40 °C 350 (690 V) 55 °C 300 (690 V) 70 °C 240
Rated Operational Current AC-3 ( $I_e$ )	(415 V) 55 °C 210 A (440 V) 55 °C 210 A (500 V) 55 °C 210 A (690 V) 55 °C 210 A (380 / 400 V) 55 °C 210 A (220 / 230 / 240 V) 55 °C 210
Rated Operational Power AC-3 ( $P_e$ )	(415 V) 110 kW (440 V) 110 kW (500 V) 132 kW (690 V) 160 kW (380 / 400 V) 110 kW (220 / 230 / 240 V) 59 kW
Rated Control Circuit Voltage ( $U_c$ )	60 Hz 220 ... 230 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 60 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 65 V-A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1350 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1550 V-A
Terminal Type	Main Circuit: Bars

---



---

**Technical UL/CSA**


---

Horsepower Rating UL/CSA	(200 V AC) Three Phase 60 hp (208 V AC) Three Phase 60 hp (220 ... 240 V AC) Three Phase 75 hp (440 ... 480 V AC) Three Phase 150 hp (550 ... 600 V AC) Three Phase 200 hp
--------------------------	--

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	2CMT2015-005436
Instructions and Manuals	N/A
RoHS Information	2CMT2015-005436

---



---

**Container Information**


---

Package Level 1 Width	203 mm
Package Level 1 Depth / Length	245 mm
Package Level 1 Height	188 mm
Package Level 1 Gross	6.1 kg

Weight

Package Level 1 EAN

7320500362372

---

### Classifications

---

Object Classification Code		Q
ETIM 4	EC000066 - Magnet contactor, AC-switching	
ETIM 5	EC000066 - Magnet contactor, AC-switching	
ETIM 6	EC000066 - Power contactor, AC switching	
ETIM 7	EC000066 - Power contactor, AC switching	
eClass		V11.0 : 27371003
IDEA Granular Category Code (IGCC)		4755 >> Contactors

---

---

### Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

