

PRODUCT-DETAILS

# A300W-20-11

## A300W-20-11 110V 50Hz / 110-120V 60Hz Contactor



### General Information

Extended Product Type	A300W-20-11
Product ID	1SFL551727R8411
EAN	7320500217412
Catalog Description	A300W-20-11 110V 50Hz / 110-120V 60Hz Contactor
Long Description	A 3-pole contactor suitable for Welding applications such as Motor starting, Isolation, By-pass and Distribution application up to max 600 V. Operated with 110 V 50Hz and 110 ... 120 V 60Hz. Equipped with 1 N.O and 1 N.C. auxiliary contacts.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

### Popular Downloads

Data Sheet, Technical Information	1SBC009400R1001
Instructions and Manuals	1SFC380003-89

### Dimensions

Product Net Width	140 mm
Product Net Depth /	180.5 mm

Length	
Product Net Height	227 mm
Product Net Weight	5,4 kg

## Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Current AC-1 (I <sub>e</sub> )	(690 V) 40 °C 500 (690 V) 55 °C 400 (690 V) 70 °C 325
Rated Operational Current AC-3 (I <sub>e</sub> )	(415 V) 55 °C 300 A (440 V) 55 °C 280 A (500 V) 55 °C 280 A (690 V) 55 °C 280 A (380 / 400 V) 55 °C 305 A (220 / 230 / 240 V) 55 °C 305
Rated Operational Power AC-3 (P <sub>e</sub> )	(415 V) 160 kW (440 V) 160 kW (500 V) 200 kW (690 V) 250 kW (380 / 400 V) 160 kW (220 / 230 / 240 V) 90 kW
Rated Control Circuit Voltage (U <sub>c</sub> )	50 Hz 110 V 60 Hz 110 ... 120 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 60 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 65 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1550 V·A
Terminal Type	Main Circuit: Bars

## Technical UL/CSA

Horsepower Rating UL/CSA	(200 V AC) Three Phase 100 hp (208 V AC) Three Phase 100 hp (220 ... 240 V AC) Three Phase 100 hp (440 ... 480 V AC) Three Phase 250 hp (550 ... 600 V AC) Three Phase 300 hp
--------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMT2015-005436
Environmental Information	1SFC101003D0201
Instructions and Manuals	1SFC380003-89
RoHS Information	2CMT2015-005436

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	203 mm
Package Level 1 Depth / Length	245 mm
Package Level 1 Height	188 mm
Package Level 1 Gross Weight	6.1 kg
Package Level 1 EAN	7320500217412

## Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
IDEA Granular Category Code (IGCC)	4755 >> Contactors

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

