

PRODUCT-DETAILS

AF750-30-00-69

AF750-30-00-69 Contactor



General Information

| | |
|-----------------------|--------------------------|
| Extended Product Type | AF750-30-00-69 |
| Product ID | 1SFL637001R6900 |
| EAN | 7320500514337 |
| Catalog Description | AF750-30-00-69 Contactor |

| | |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Long Description | <p>The AF750-30-00-69 is a 3 pole - 1000 V IEC or 600 V UL contactor with Main Circuit Bars, controlling motors up to 400 kW / 400 V AC (AC-3) or 600 hp / 480 V UL and switching power circuits up to 1050 A (AC-1) or 900 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p> |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|--------------------------|---------------|
| Instructions and Manuals | 1SFC380023-en |
|--------------------------|---------------|

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 210 mm |
| Product Net Depth / Length | 242 mm |
| Product Net Height | 283 mm |
| Product Net Weight | 13.6 kg |

Technical

| | |
|--------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Number of Auxiliary Contacts NC | 0 |
| Rated Operational Current AC-1 (I _e) | (1000 V) 40 °C 1000 A (1000 V) 55 °C 875 A (1000 V) 70 °C 720 A (690 V) 40 °C 1050 (690 V) 55 °C 875 (690 V) 70 °C 720 |
| Rated Operational Current AC-3 (I _e) | (415 V) 55 °C 750 A (440 V) 55 °C 750 A (500 V) 55 °C 750 A (690 V) 55 °C 650 A (1000 V) 55 °C 300 A (380 / 400 V) 55 °C 750 A (220 / 230 / 240 V) 55 °C 750 |
| Coil Consumption | Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V-A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1100 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1100 V-A Pull-in at Max. Rated Control Circuit Voltage DC 1020 V-A |

Technical UL/CSA

| | |
|----------------------------------|---------------------------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 1000 V |
| General Use Rating UL/CSA | (1000 V AC) 900 A (600 V AC) 900 A |

Environmental

| | |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

Certificates and Declarations (Document Number)

| | |
|---------------------------------|--------------------------------------------|
| ABS Certificate | 15-LD1408622-PDA |
| BV Certificate | BV_13409-COBV |
| CB Certificate | SE-82863 |
| CCS Certificate | GB14T00030 |
| CQC Certificate | CQC2007010304256684 CQC2012010304540080 |
| cUL Certificate | UL_20111101-E36588 |
| Declaration of Conformity - CCC | 2020980304001301 2020980304001045 |
| Declaration of Conformity - CE | 2CMT2019-005796 |

| | |
|---------------------------|-------------------|
| DNV GL Certificate | TAE00001W1 |
| EAC Certificate | 9AKK107046A8618 |
| Environmental Information | 1SAC200044H0006 |
| Instructions and Manuals | 1SFC380023-en |
| LR Certificate | 16-20064 |
| PRS Certificate | TE_2092_880423_16 |
| RINA Certificate | ELE060313XG_002 |
| RMRS Certificate | 9AKK107045A6978 |
| RoHS Information | 2CMT2019-005796 |
| UL Listing Card | UL_E36588 |

Container Information

| | |
|--------------------------------|--------|
| Package Level 1 Width | 280 mm |
| Package Level 1 Depth / Length | 375 mm |
| Package Level 1 Height | 310 mm |
| Package Level 1 Gross Weight | 15 kg |

Classifications

| | |
|------------------------------------|------------------------------------------|
| Object Classification Code | Q |
| ETIM 6 | EC000066 - Power contactor, AC switching |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| IDEA Granular Category Code (IGCC) | 4755 >> Contactors |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

