


PRODUCT-DETAILS

# 8114.5

## 8114.5 Card switch 1-gang, 1-way, SP w/ time delay



### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | 8114.5   |
| Product ID            | 2CLA811450A1001  |
| EAN                   | 8427238064703  |
| Catalog Description   | 8114.5 Card switch 1-gang, 1-way, SP w/ time delay   |
| Long Description      | <p>Rated voltage: 110 - 250 Vac; 50/60 Hz</p> <p>Rated current:</p> <ul style="list-style-type: none"> <li>- Incandescent/halogen: 3.000W@230Vac / 1.600W@127Vac</li> <li>- Fluorescent: 1.300VA@230Vac / 700VA@127Vac</li> </ul> <p>- Electronic and ferromag. transf. and motors: 3.000VA@230Vac / 1.600VA@127Vac</p> <p>3 wire connection (neutral conductor required)</p> <p>For 54mm width cards</p> <p>Locator LED lamp included</p> <p>Time delayed switch: 5 - 90 seconds</p> <p>Cover plate code: 8514, 8414, 8214 &amp; 5514</p> |

### Technical

|                                 |   |
|---------------------------------|---|
| Product Name                    | Card switch 1-gang, 1-way, SP w/ time delay |
| Rated Voltage (U <sub>r</sub> ) | 230 V                                       |
| Rated Current (I <sub>n</sub> ) | 16 A  |
| Frequency (f)                   | 50...60 Hz                                  |
| Minimum Switching Capacity      | 3000...3000 W                               |
| Load Type                       | Universal                                   |
| Mounting Type                   | Flush mounted (plaster)                     |
| Type of Fastening               | Mounting with Screw                         |

|                     |   |
|---------------------|---|
| Number of Batteries | 0 |
|---------------------|---|

## Environmental

|                         |  |
|-------------------------|--|
| Ambient Air Temperature | Operation -5 ... +35 °C<br>Storage -5 ... +50 °C |
|-------------------------|--|

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 0.076 m  |
| Product Net Height         | 0.064 m  |
| Product Net Depth / Length | 0.076 m  |
| Product Net Weight         | 0.078 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 0.076 m       |
| Package Level 1 Height         | 0.064 m       |
| Package Level 1 Depth / Length | 0.076 m       |
| Package Level 1 Gross Weight   | 0.078 kg      |
| Package Level 1 EAN            | 8427238064703 |

## Ordering

|                         |            |
|-------------------------|------------|
| Minimum Order Quantity  | 1 piece    |
| Customs Tariff Number   | 85365080   |
| Country of Origin       | Spain (ES) |
| Selling Unit of Measure | piece      |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A1745 |
| Instructions and Manuals       | 2CLX811459A1001 |

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107046A0356 |
| Instructions and Manuals          | 2CLX811459A1001 |

## Classifications

|                |  |
|----------------|--|
| ETIM 6         | EC001588 - Electronic switch                               |
| ETIM 7         | EC001588 - Electronic switch                               |
| ETIM 8         | EC001588 - Electronic switch                               |
| WEEE Category  | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer                                       |
| CN8            | 85365080   |

---

## Categories

---

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → Hotel Functions

