

PRODUCT-DETAILS

8161

8161 Relay switch



General	Information	

Extended Product Type	8161	
Product ID	2CLA816100A1001	
EAN	8427238016818	
Catalog Description	8161 Relay switch	

Rated voltage: 230 V~, +10 % / -10 % Rated frequency: 50 Hz - 60 Hz 3 wire connection (neutral conductor required).

For timer control element 8165.31 or 8165.3

Operation also possible via conventional push buttons 8104.X.

low-voltage halogen lamps, that are operated via transformers.

Rated current: 10 AX

Rated power: 2300 W/VA

Temperature range (Device): -25 °C to 55 °C

Included: fixing claws

Long Description

Technical	
Product Name	Relay switch
Rated Voltage (U _r)	230 V
Rated Current (In)	10 A
Frequency (f)	5050 Hz
Minimum Switching Capacity	23002300 W
Load Type	Universal
Mounting Type	Flush mounted (plaster)

ETIM 8

WEEE Category

Type of Fastening	Mounting with Screw
Model Number	Relay
Number of Batteries	0
Environmental	
Ambient Air	Operation -5 +35 °C
Temperature	Storage -5 +50 °C
Dimensions	
Product Net Width	0.062 m
Product Net Height	0.073 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.14 kg
Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width Package Level 1 Height	0.062 m 0.073 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	8427238016818
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Germany (DE)
Selling Unit of Measure	piece
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	No declaration needed
Instructions and	No document needed
Manuals	
Popular Downloads	
Data Sheet, Technical Information	9AKK107046A0356
Instructions and Manuals	No document needed
THE	
Classifications	
ETIM 6	EC001588 - Electronic switch
ETIM 7	EC001588 - Electronic switch
ETIM C	ECONIENO Electronia curitale

EC001588 - Electronic switch

5. Small Equipment (No External Dimension More Than 50 cm)

8161

WEEE B2C / B2B	Business To Consumer
CN8	85365080
UNSPSC	39122200

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Arco \rightarrow Flush\ Mounted\ Inserts \rightarrow Electronic\ Switch\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Olas \rightarrow Flush\ Mounted\ Inserts \rightarrow Electronic\ Switch\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Sky \rightarrow Flush\ Mounted\ Inserts \rightarrow Electronic\ Switch\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Tacto \rightarrow Flush\ Mounted\ Inserts \rightarrow Electronic\ Switch\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Light\ /\ LoadControl \rightarrow Electronic\ Push\ Button \rightarrow Electronic\ Push\ Button \rightarrow Electronic\ Switch\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Light\ /\ LoadControl \rightarrow Movement\ Detectors \rightarrow Movement\ Detectors - Flush\ Mounted \rightarrow Electronic\ Switch\ Inserts$

