

PRODUCT-DETAILS

8181.2

8181.2 Beacon LED light



General Information	
Extended Product Type	8181.2
Product ID	2CLA818120A1001
EAN	8427238063195
Catalog Description	8181.2 Beacon LED light
Long Description	Rated voltage: 230 Vac / 50 Hz Lamp: blue and high luminosity white LED (selectable with rotatory switch) Luminous flux: > 2 lumen at 1 meter White diffuser Autonomy: 3 hours (1 hour at maximum illumination 2 hours with lower illumination) Battery: Ni-MH (estimated lifetime: 4 years).

Beacon LED light
Escape route lighting/signage
230230 V
AC
7 W
Peripheral (Individual Battery)
2
1
1
Automatic Self Test

Wiring Configuration	Wiring system: Continuous circuit/emergency circuit Type of wiring: Ending
Ballast Type	Current Controlled
Connection Type	Screw
Lamp Type	LED not exchangeable
Light Distribution Type	Diffuser Lens Optic Panel
Marking Type	Sticker
Mounting Type	Built-in
Type of Indicator	Only single-sided
Cover Material	Plastic, Transparent
Housing Material	Plastic
Illuminance	2 lm
Housing Color	Black
Battery Chemical Composition	Nickel-Metal Hydride
Battery Type	Portable
Battery Weight	0.04 kg
Number of Batteries	1

Environmental

Ambient Air Temperature	Operation -5 +35 °C Storage -5 +50 °C
Degree of Protection	IP20
Protection Class	Isolated

Dimensions Product Net Width 73 mm Product Net Height 52 mm Product Net Depth / Length 0.073 m Length 0.085 kg Product Net Weight 0.085 kg Product Net Length 44 mm Built-In Depth (t₂) 42 mm

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.052 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.085 kg
Package Level 1 EAN	8427238063195

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Spain (ES)
Selling Unit of Measure	piece

8181.2

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CLX818139A1001

Popular Downloads	
Data Sheet, Technical Information	9AKK107046A0356
Instructions and Manuals	2CLX818139A1001

Classifications	
ETIM 6	EC001957 - Emergency luminaire
ETIM 7	EC001957 - Emergency luminaire
ETIM 8	EC000064 - Information light signal for domestic switching devices
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85365080
UNSPSC	39111709

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Arco \rightarrow Flush\ Mounted\ Inserts \rightarrow LED\ Light\ /\ Light\ Signal\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Olas \rightarrow Flush\ Mounted\ Inserts \rightarrow LED\ Light\ /\ Light\ Signal\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Sky \rightarrow Flush\ Mounted\ Inserts \rightarrow LED\ Light\ /\ Light\ Signal\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Tacto \rightarrow Flush\ Mounted\ Inserts \rightarrow LED\ Light\ /\ Light\ Signal\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow LED\ Light\ /\ Light\ Signals \rightarrow LED\ Light\ /\ Light\ Signal \rightarrow LED\ Light\ /\ Light\ Signal\ -\ Flush\ Mounted \rightarrow LED\ Light\ /\ Light\ Signal\ Inserts$

