

PRODUCT-DETAILS

8185

8185 USB charger 1.500mA, 2 outlets



General Information	
Extended Product Type	818
Product ID	2CLA818500A100
EAN	8427238107103
Catalog Description	8185 USB charger 1.500mA, 2 outlets
Long Description	Input voltage: 100 - 240 Vac ±10%; 50/60 H: Input current: 0,20 A (with maximum load) Output voltage: 5 Vdc ±5% Output current: 1.500 mA (total for both gangs Power consumption in stand-by: <= 0,3W@230Vac Energy efficiency: >= 71% Operating temperature: 0°C to 35°C Without fixing claws
	Cover plate code: 8585, 8685, 8485, 8285 & 5585

Technical	
Product Name	USB charger 1.500mA, 2 outlets
Operational Voltage	100240 V
Output Current Maximum (I _{out})	1500 mA
Frequency (f)	5060 Hz
Number of Outputs	2
Mounting Type	Flush mounted (plaster)
Model Number	Breakout cable
Number of Batteries	0

8185	
Environmental	
Ambient Air Temperature	Operation -5 +35 °(Storage -5 +50 °(
Dimensions	
Product Net Width	0.073 n
Product Net Height	0.052 n
Product Net Depth / Length	0.073 n
Product Net Weight	0.069 kg
Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.052 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.073 kg
Package Level 1 EAN	8427238107103
Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85043180
Country of Origin	Viet Nam (VN)
Selling Unit of Measure	piece
Certificates and Declarations (Document Num	ber)
Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CLX228519N1001
Popular Downloads	
Data Sheet, Technical Information	9AKK107046A0356
Instructions and	2CI Y228519N100

Information	
Instructions and	2CLX228519N1001
Manuals	

Classifications	
ETIM 6	EC002949 - USB power supply
ETIM 7	EC002949 - USB power supply
ETIM 8	EC002949 - USB power supply
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85043180
UNSPSC	39121406

8185

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Charging\ Devices \rightarrow Cha$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Arco \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Olas \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Sky \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Tacto \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

