

PRODUCT-DETAILS

ABB420MF5W

Mechanical Interlocked Fused 20A 3P4W 3ph
600V, UL/CSA approved and CE compliant



General Information

Extended Product Type	ABB420MF5W
Product ID	2CMA100517R1000
EAN	7392696005173
Catalog Description	Mechanical Interlocked Fused 20A 3P4W 3ph 600V, UL/CSA approved and CE compliant
Long Description	Mechanical Interlocked Fused 20A 3P4W 3ph 600V Clock Position Of Grounding Contact 5 hour Color code Black, UL/CSA approved and CE compliant

Ordering

EAN	7392696005173
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	160 mm
Product Net Height	103 mm
Product Net Weight	1.83 kg

Container Information

Package Level 1 Width	169 mm
Package Level 1 Depth / Length	339 mm
Package Level 1 Height	219 mm
Package Level 1 Gross Weight	1.83 kg
Package Level 1 EAN	7392696005173
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CSA Certificate	2CHC660172X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0022
UL Certificate	E109667-20021206
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Entry Position	Other
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Switched interlocked socket outlets
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB420MF5W
Mounting Holes	130x225
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CMF
Product Name	Switched interlocked socket outlet
Protection Type	Watertight
Rated Current (I_n)	20 A
Rated Voltage (U_r)	600 ... 690 V
Recommended Screw	PH2

Driver	
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700054M0001
Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39122205

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

