

PRODUCT-DETAILS

# ABB460MF5W

Mechanical Interlock Fused 60A 3P4W 3phase 600V, UL/CSA approved and CE compliant



## General Information

Extended Product Type	ABB460MF5W
Product ID	2CMA100529R1000
EAN	7392696005296
Catalog Description	Mechanical Interlock Fused 60A 3P4W 3phase 600V, UL/CSA approved and CE compliant
Long Description	Mechanical Interlock Fused 60A 3P4W 3phase 600V Clock Position Of Grounding Contact 5 hour Color code Black, UL/CSA approved and CE compliant

## Ordering

EAN	7392696005296
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

## Dimensions

Product Net Width	175 mm
Product Net Height	241 mm
Product Net Weight	2.5 kg

---

**Container Information**


---

Package Level 1 Width	169 mm
Package Level 1 Depth / Length	339 mm
Package Level 1 Height	219 mm
Package Level 1 Gross Weight	2.5 kg
Package Level 1 EAN	7392696005296
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	90 kg
Package Level 2 EAN	7392696064620
Package Level 2 Units	pallet (lift) 28 piece

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

**Certificates and Declarations (Document Number)**


---

CSA Certificate	2CHC660172X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0022
UL Certificate	E109667-20021206
REACH Declaration	2CMC700005D0022

---



---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm <sup>2</sup>
Cable Entry Position	Other
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Switched interlocked socket outlets
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB460MF5W
Mounting Holes	378x145, 128x145
Number of Poles	4

Order Multiple	1 piece
Product Main Type	CMF
Product Name	Switched interlocked socket outlet
Protection Type	Watertight
Rated Current ( $I_n$ )	60 A
Rated Voltage ( $U_r$ )	600 ... 690 V
Recommended Screw Driver	PH2
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700054M0001
Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

## Classifications

eClass	27440510
UNSPSC	39122205

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

