

PRODUCT-DETAILS

ABB532R6W

IEC Receptacle 32A 4P5W 220/380V & 240/415V, UL/CSA approved and CE compliant



General Information

Extended Product Type	ABB532R6W
Product ID	2CMA100576R1000
EAN	7392696005760
Catalog Description	IEC Receptacle 32A 4P5W 220/380V & 240/415V, UL/CSA approved and CE compliant
Long Description	IEC Receptacle 32A 4P5W 220/380V & 240/415V Clock Position Of Grounding Contact 6 hour Color code Red, UL/CSA approved and CE compliant

Ordering

EAN	7392696005760
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	95 mm
Product Net Height	109 mm
Product Net Weight	0.32 kg

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.37 kg
Package Level 1 EAN	7392696005760
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	149.5 kg
Package Level 2 EAN	7392696064798
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CSA Certificate	2CHC660175X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0022
UL Certificate	E163435-19950105
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Receptacle
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB532R6W
Mounting Holes	79.5x79.5

Mounting Type	unified flange, angled
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRAU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I_n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700052M0001
Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Socket Outlets for Panel Mounting

