

PRODUCT-DETAILS

ABB330B5W

ABB330B5W Panel mounted inlet



General Information

Extended Product Type	ABB330B5W
Product ID	2CMA100666R1000
EAN	7392696006668
Catalog Description	ABB330B5W Panel mounted inlet
Long Description	IEC Inlet 30A 2P3W 277V Clock Position Of Grounding Contact 5 hour Color code Grey, UL/CSA approved and CE compliant

Ordering

EAN	7392696006668
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	94 mm
Product Net Height	94 mm
Product Net Weight	0.303 kg

Container Information

Package Level 1 Width	112 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	139 mm
Package Level 1 Gross Weight	0.303 kg
Package Level 1 EAN	7392696006668
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	126.05 kg
Package Level 2 EAN	7392696064934
Package Level 2 Units	pallet (lift) 350 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CSA Certificate	2CHC660174X0201
Declaration of Conformity - CE	2CMC700005D0022
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0022
UL Certificate	E109550-19950105
REACH Declaration	2CMC700005D0022

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Color	Grey
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#ABB330B5W

Mounting Holes	79,5x79,5
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TBAU
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	30 A
Rated Frequency (f)	50 ... 60 Hz
Rated Voltage (U_r)	277 V
Recommended Screw Driver	PH2
Standards	UL 1682, 1686 / CSA C22.2 No. 182.1-13
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700052M0001
Installation Manual	2CMC700052M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440519
UNSPSC	39121402

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Inlets for Panel Mounting

