

PRODUCT-DETAILS

ABB516MI6WN

Industrial Switched Interlocked Socket Outlets, 3P+N+E, 6 hour, Red, IP67, 16A, 200/346 ... 240/415V, UL/CSA approved and CE compliant



General Information

| | |
|-----------------------|--|
| Extended Product Type | ABB516MI6WN |
| Product ID | 2CMA105094R1000 |
| EAN | 7392696050944 |
| Catalog Description | Industrial Switched Interlocked Socket Outlets, 3P+N+E, 6 hour, Red, IP67, 16A, 200/346 ... 240/415V, UL/CSA approved and CE compliant |
| Long Description | IEC Mechanical interlock for 16A and 200/346-240/415V AC 4P5W, UL/CSA/NSF approved and CE compliant |

Ordering

| | |
|------------------------|---------------------|
| EAN | 7392696050944 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|----------|
| Product Net Width | 160 mm |
| Product Net Height | 205 mm |
| Product Net Weight | 1.040 kg |

Container Information

| | |
|-----------------------|--------|
| Package Level 1 Width | 339 mm |
|-----------------------|--------|

| | |
|--------------------------------|---------------|
| Package Level 1 Depth / Length | 219 mm |
| Package Level 1 Height | 169 mm |
| Package Level 1 Gross Weight | 0.7 kg |
| Package Level 1 EAN | 7392696058759 |
| Package Level 1 Units | box 1 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|------------------|
| CSA Certificate | 2CHC660172X0201 |
| Declaration of Conformity - CE | 2CMC700005D0022 |
| Environmental Information | 2CMC000057M0000 |
| RoHS Information | 2CMC700005D0022 |
| UL Certificate | E109667-20021206 |
| REACH Declaration | 2CMC700005D0022 |

Additional Information

| | |
|---------------------------------|---|
| Additional Information | 3P+N+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 1 ... 4 mm ² |
| Cable Entry Position | Other |
| Color | Red |
| Connection Type | Screw |
| Degree of Protection | IP67 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Mechanical Interlock Receptacle |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#ABB516MI6WN |
| Mounting Holes | 130x225 |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | CMVS |
| Product Name | Industrial Switched Interlocked Socket Outlet |
| Rated Current (I _n) | 16 A |
| Rated Voltage (U _r) | 200/346 ... 240/415 V |
| Standards | UL 1682, 1686 / CSA C22.2 No. 182.1-13 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC000028M0001 |
| Installation Manual | 2CMC000028M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39122221 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 14 ... 12 AWG |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

