

PRODUCT-DETAILS

ABB560MI5WN

Industrial Switched Interlocked Socket Outlets,
3P+N+E, 5 hour, Black, IP67, 60A, 347/600V,
UL/CSA approved and CE compliant



General Information

| | |
|-----------------------|--|
| Extended Product Type | ABB560MI5WN |
| Product ID | 2CMA105169R1000 |
| EAN | 7392696051699 |
| Catalog Description | Industrial Switched Interlocked Socket Outlets, 3P+N+E, 5 hour, Black, IP67, 60A, 347/600V, UL/CSA approved and CE compliant |
| Long Description | IEC Mechanical interlock for 60A and 347/600V AC 4P5W, UL/CSA/NSF approved and CE compliant |

Ordering

| | |
|------------------------|---------------------|
| EAN | 7392696051699 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|----------|
| Product Net Width | 175 mm |
| Product Net Height | 241 mm |
| Product Net Weight | 2.500 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 495 mm |
| Package Level 1 Depth / Length | 268 mm |
| Package Level 1 Height | 185 mm |
| Package Level 1 Gross Weight | 2.5 kg |
| Package Level 1 EAN | 7392696051699 |
| Package Level 1 Units | box 1 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|------------------|
| CSA Certificate | 2CHC660172X0201 |
| Declaration of Conformity - CE | 2CMC700005D0022 |
| Environmental Information | 2CMC000057M0000 |
| RoHS Information | 2CMC700005D0022 |
| UL Certificate | E109667-20021206 |
| REACH Declaration | 2CMC700005D0022 |

Additional Information

| | |
|---------------------------------|---|
| Additional Information | 3P+N+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 6 ... 25 mm ² |
| Cable Entry Position | Other |
| Color | Black |
| Connection Type | Screw |
| Degree of Protection | IP67 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Outlet |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | Ind. P&S#ABB560MI5WN |
| Mounting Holes | 378x145, 128x145 |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | CMVS |
| Product Name | Industrial Switched Interlocked Socket Outlet |
| Rated Current (I _n) | 60 A |
| Rated Voltage (U _r) | 600 ... 690 V |
| Standards | UL 1682, 1686 / CSA C22.2 No. 182.1-13 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |

| | |
|--------------------------|------------------------|
| Instructions and Manuals | 2CMC000028M0001 |
| Installation Manual | 2CMC000028M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39122221 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 8 ... 4 AWG |
| Tightening Torque | WireClamp3.5 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

