

PRODUCT-DETAILS

ACS580-01-073A-4

ACS580-01-073A-4 PN: 37 kW, IN: 73 A



General Information		
Global Commercial Alias	ACS580-01-073A-4	
Product ID	3AUA0000080499	
ABB Type Designation	ACS580-01-073A-4	
EAN	6438177305552	
Catalog Description	ACS580-01-073A-4 PN: 37 kW, IN: 73 A	

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Complete Drive Module Efficiency (61800-9-2)

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	289 W	0.6 %	90.3 %
0 / 50 %	386 W	0.8 %	93.1 %
0 / 100 %	720 W	1.4 %	93.5 %
50 / 25 %	318 W	0.6 %	94.6 %
50 / 50 %	448 W	0.9 %	96.0 %
50 / 100 %	860 W	1.7 %	96.2 %
90 / 50 %	522 W	1.0 %	97.4 %
90 / 100 %	1114 W	2.2 %	97.2 %

Ordering		
Customs Tariff Number	85044084	
EAN	6438177305552	
Quote Only	No	
Made To Order	Yes	
Selling Unit of Measure	piece	
Minimum Order Quantity	1 piece	
Order Multiple	1 piece	

Container Information	
Gross Volume	96.93 m³

Dimensions		
Product Net Height	636 mm	
Product Net Length	257 mm	
Product Net Weight	19 kg	
Product Net Width	203 mm	

50/60 Hz
380 480 V
Wall-mounted
3
No
MODBUS DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP

ACS580-01
Frequency converter

Classifications

Categories











