


PRODUCT-DETAILS

3GAA051311-BSF

No Description Available



General Information

Product ID	3GAA051311-BSF
ABB Type Designation	M3AA 56A 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 56A 2
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.09 kW	2800 r/min	0.35 A	0.670	55.60 %	0.29 N-m	3.50
D	--	50 Hz	230 V	0.09 kW	2800 r/min	0.60 A	0.670	55.60 %	0.29 N-m	3.50
Y	--	60 Hz	460 V	0.09 kW	3430 r/min	0.33 A	0.600	56.80 %	0.23 N-m	3.90

Gross Weight	0 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class NA

	Full Load (100%) 55.6 % Partial Load (75%) 50.8 % Partial Load (50%) 38.7 %
IE Class Data (60 Hz)	IE Class NA Full Load (100%) 56.8 % Partial Load (75%) 50.6 % Partial Load (50%) 40.5 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	2.8 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA051001-BSE
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

