



PRODUCT-DETAILS

3GAA052002-CSA

M2AA 56B 4

For sale but "Obsolete", replaced by

General Information

Product ID	3GAA052002-CSA
ABB Type Designation	M2AA 56B 4
Catalog Description	M2AA 56B 4

Additional Information

ABB Type Designation	M2AA 56B 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6201-2Z C3
Bearing NDE	6201-2Z C3
Country of Origin	Romania (RO) Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque
D	--	50 Hz	230 V	0.09 kW	1370 r/min	0.65 A	0.620	55.50 %	0.62 N·m
Y	--	50 Hz	400 V	0.09 kW	1370 r/min	0.37 A	0.620	55.50 %	0.62 N·m
Y	--	60 Hz	460 V	0.11 kW	1630 r/min	0.36 A	0.660	57.10 %	0.61 N·m

Gross Weight	3.66 kg
IC Class	IC411
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 56B 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00018 kg/m ³
Number of Poles (High)	4
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	3.4 kg
Product Type	2AA2__M2AA__IE2_AA
Quote Only	No
Replaced Product ID	3GVA052002-CSA

(OLD)

Replacement Product ID (NEW)	3GAA052312-CSF
Selling Unit of Measure	piece
Sound dB (A)	36 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)