



PRODUCT-DETAILS

3GAA061001-BSC

M2AA 63A 2

For sale but "Obsolete", replaced by

General Information

Product ID	3GAA061001-BSC
ABB Type Designation	M2AA 63A 2
EAN	AA061001-BSC
Catalog Description	M2AA 63A 2

Additional Information

ABB Type Designation	M2AA 63A 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6202-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	Romania (RO)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EAN	AA061001-BSC

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency
D	--	50 Hz	230 V	0.18 kW	2820 r/min	0.97 A	0.620	75.00 %
Y	--	50 Hz	400 V	0.18 kW	2820 r/min	0.55 A	0.620	75.00 %
Y	--	60 Hz	460 V	0.22 kW	3370 r/min	0.54 A	0.670	75.80 %

Gross Weight	3.9 kg
IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 63A 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00013 kg/m ³
Number of Poles (High)	2
Output Power	0.25 kW
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	3.9 kg

Product Type	2AA2_M2AA_IE2_AA
Quote Only	No
Replacement Product ID (NEW)	3GAA061311-BSF
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)