


PRODUCT-DETAILS

3GAA061313-CSF

No Description Available



General Information

Product ID	3GAA061313-CSF
ABB Type Designation	M3AA 63C 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 63C 2
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.37 kW	2750 r/min	0.96 A	0.780	69.50 %	1.28 N-m	4.70
D	--	50 Hz	230 V	0.37 kW	2750 r/min	1.66 A	0.780	69.50 %	1.28 N-m	4.70
Y	--	60 Hz	460 V	0.37 kW	3535 r/min	0.85 A	0.720	72.00 %	1.00 N-m	5.60

Gross Weight	7.6 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 69.5 %

	Partial Load (75%) 68.8 % Partial Load (50%) 63.2 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 72.0 % Partial Load (75%) 70.2 % Partial Load (50%) 63.9 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GAA061313-BSF
Product Name	3-Phase squirrel cage motor
Product Net Weight	4.6 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA061003-CSE 3GVA061003-CSC 3GAA061003-CSC
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

