



PRODUCT-DETAILS

3GAA063001-BSC

M2AA 63A 6

For sale but "Obsolete", replaced by

General Information

Product ID	3GAA063001-BSC
ABB Type Designation	M2AA 63A 6
Catalog Description	M2AA 63A 6

Additional Information

ABB Type Designation	M2AA 63A 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6202 2Z C3
Bearing NDE	6201 2Z C3
Country of Origin	Romania (RO)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque
D	--	50 Hz	230 V	0.09 kW	910 r/min	0.85 A	0.560	47.10 %	0.94 N·m
Y	--	50 Hz	400 V	0.09 kW	910 r/min	0.49 A	0.560	47.10 %	0.94 N·m
Y	--	60 Hz	460 V	0.11 kW	1080 r/min	0.47 A	0.590	49.60 %	0.92 N·m

Gross Weight	4 kg
IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 63A 6
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00020 kg/m ³
Number of Poles (High)	6
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	4 kg
Product Type	2AA2_M2AA_IE2_AA
Quote Only	No
Replacement Product ID (NEW)	3GAA063311-BSF

Selling Unit of Measure	piece
Sound dB (A)	38 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Vittuone, Italy
Temperature Class Default	--
Temperature Rise	70 K
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)