


PRODUCT-DETAILS

3GAA063001-BSE

M2AA 63 A 6

For sale but "Obsolete", replaced by



General Information

Product ID	3GAA063001-BSE
ABB Type Designation	M2AA 63 A 6
Catalog Description	M2AA 63 A 6

Additional Information

ABB Type Designation	M2AA 63 A 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	230 V	0.09 kW	890 r/min	0.71 A	0.620
Y	--	50 Hz	400 V	0.09 kW	890 r/min	0.41 A	0.620
Y	--	60 Hz	460 V	0.09 kW	1110 r/min	0.38 A	0.550

Gross Weight	4 kg
IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55

Insulation Class	ICLF
Invoice Description	M2AA 63 A 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	4 kg
Product Type	2AA2_M2AA_IE2_AA
Quote Only	No
Replacement Product ID (NEW)	3GAA063311-BSF
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors

