



PRODUCT-DETAILS

3GAA063312-BSC

M3AA 63B 6

For sale but "Obsolete", replaced by

General Information

| | |
|----------------------|----------------|
| Product ID | 3GAA063312-BSC |
| ABB Type Designation | M3AA 63B 6 |
| Catalog Description | M3AA 63B 6 |

Additional Information

| | |
|-----------------------|--------------|
| ABB Type Designation | M3AA 63B 6 |
| Altitude | 1000 m |
| Ambient Temperature | 40 °C |
| Bearing | 6202-2ZC3 |
| Bearing NDE | 6201-2ZC3 |
| Country of Origin | Romania (RO) |
| Customs Tariff Number | 85015100 |
| Direction of Rotation | Both sides |

Electrical Data

| Conn | Temp Class | Freq | Voltage | Power | Speed | Current | Power Factor | Torque |
|------|------------|-------|---------|---------|-----------|---------|--------------|----------|
| D | -- | 50 Hz | 230 V | 0.12 kW | 910 r/min | 0.88 A | 0.580 | 1.25 N-m |
| Y | -- | 50 Hz | 400 V | 0.12 kW | 910 r/min | 0.51 A | 0.580 | 1.25 N-m |
| Y | -- | 50 Hz | 415 V | 0.12 kW | 925 r/min | 0.56 A | 0.540 | 1.23 N-m |

| | |
|------------------------------|-----------------------------|
| Gross Weight | 4.7 kg |
| IC Class | IC411 |
| IM Class | IMB5 IM3001 |
| IP Class | IP55 |
| Insulation Class | ICLF |
| Invoice Description | M3AA 63B 6 |
| Lubrication | For life |
| Made To Order | No |
| Minimum Order Quantity | 1 piece |
| Number of Poles (High) | 6 |
| Package Level 1 Units | 0 carton |
| Product Name | 3-Phase squirrel cage motor |
| Product Net Weight | 4.5 kg |
| Product Type | 3AA2_M3AA_IE2_AA |
| Quote Only | No |
| Replacement Product ID (NEW) | 3GAA063312-BSF |
| Selling Unit of Measure | piece |

| | |
|------------------------------|--|
| Standards | IEC 60034-1 |
| Starting of Motor | Direct Online |
| Stocked At (Warehouses) | Vittuone, Italy |
| Temperature Class Default | -- |
| Terminator Box Location | D-End top |
| Two Speed Motor | No |
| Type of Duty | S1 |
| UNSPSC | 26101100 |
| Voltage Code | S |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |