


PRODUCT-DETAILS

3GAA063313-BSF

No Description Available



General Information

Product ID	3GAA063313-BSF
ABB Type Designation	M3AA 63C 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 63C 6
Bearing	6201-2Z/C3
Bearing NDE	6201-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.18 kW	880 r/min	0.72 A	0.620	56.60 %	1.96 N·m	2.80
D	--	50 Hz	230 V	0.18 kW	880 r/min	1.16 A	0.620	58.10 %	1.96 N·m	2.80
Y	--	60 Hz	460 V	0.18 kW	1110 r/min	0.66 A	0.560	55.00 %	1.56 N·m	3.70

Gross Weight	6.3 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 53.7 % Partial Load (75%) 52.7 % Partial Load (50%) 46.8 %

IE Class Data (60 Hz)

IE Class IE2
 Full Load (100%) 55.0 %
 Partial Load (75%) 51.6 %
 Partial Load (50%) 43.3 %

IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	5.3 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA063003-BSE 3GVA063003-BSC 3GAA063003-BSC
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany Vittuone, Italy
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

