



PRODUCT-DETAILS

3GAA071061-CSA

M1AA 71A 2

General Information

Product ID	3GAA071061-CSA
ABB Type Designation	M1AA 71A 2
Catalog Description	M1AA 71A 2

Additional Information

ABB Type Designation	M1AA 71A 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6202-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Turkey (TR)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	230 V	0.37 kW	2800 r/min	1.85 A	0.800
Y	--	50 Hz	400 V	0.37 kW	2800 r/min	1.07 A	0.800
Y	--	60 Hz	460 V	0.37 kW	3390 r/min	0.92 A	0.770

Gross Weight	0 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class NA Full Load (100%) 65.7 % Partial Load (75%) 66.7 % Partial Load (50%) 63.2 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M1AA 71A 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	0 kg
Product Type	1AA1__M1AA_IE1_AA
Quote Only	No

Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)