



PRODUCT-DETAILS

3GAA071313-CBEBR1

No Description Available

General Information

Product ID	3GAA071313-CBEBR1
ABB Type Designation	M3AA 71C 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3AA 71C 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2Z/C3
Bearing NDE	6202-2Z/C3
Country of Origin	Sweden (SE)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	60 Hz	440 V	0.75 kW	3470 r/min	1.70 A	0.720	80.10 %	2.00 N·m	7.80

Gross Weight	7.5 kg
IC Class	IC411
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 80.1 % Partial Load (75%) 78.4 % Partial Load (50%) 72.9 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00056 kg/m ³
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	6.5 kg
Product Type	3AA2_M3AA_IE2_AA

Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	61 dB(A)
Standards	IEC 60034-1
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	B
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)