


PRODUCT-DETAILS

3GAA072312-ABE

M3AA 71B 4



General Information

Product ID	3GAA072312-ABE
ABB Type Designation	M3AA 71B 4
Catalog Description	M3AA 71B 4

Additional Information

ABB Type Designation	M3AA 71B 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203-2ZC3
Bearing NDE	6202-2ZC3
Country of Origin	Italy (IT) Romania (RO)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Torque
D	--	60 Hz	440 V	0.37 kW	1600 r/min	0.86 A	0.800	2.30 N·m

Gross Weight	6.2 kg
IC Class	IC411
IM Class	IMB3 IM1001
IP Class	IP55

Insulation Class	ICLF
Invoice Description	M3AA 71B 4
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	5.9 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	B
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

