



PRODUCT-DETAILS

3GAA091001-ADE

M2AA 90S 2

General Information

Product ID	3GAA091001-ADE
ABB Type Designation	M2AA 90S 2
Catalog Description	M2AA 90S 2

Additional Information

ABB Type Designation	M2AA 90S 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Spain (ES) China (CN) Sweden (SE) Poland (PL)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	1.50 kW	2895 r/min	2.13 A	0.750	78.50 %	4.90 N·m	6.40
D	--	50 Hz	400 V	1.50 kW	2895 r/min	3.60 A	0.750	78.50 %	4.90 N·m	6.40
D	--	60 Hz	460 V	1.50 kW	3510 r/min	3.00 A	0.760	81.70 %	4.00 N·m	7.30

Gross Weight	16 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 78.5 % Partial Load (75%) 77.2 % Partial Load (50%) 71.6 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 81.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 90S 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece

Number of Poles (High)	2
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	13 kg
Product Type	2AA1__M2AA_IE1_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA091061-ADA 3GAA091001-ADA
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Legacy IEC Low Voltage Motors → Aluminum Motors

Motors and Generators → IEC Low Voltage AC Motors → Marine Motors → Marine General Performance Motors