



PRODUCT-DETAILS

3GAA091001-NSEAL2

M2AA 90S 2

General Information

Product ID	3GAA091001-NSEAL2
ABB Type Designation	M2AA 90S 2
Catalog Description	M2AA 90S 2

Additional Information

ABB Type Designation	M2AA 90S 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Spain (ES) Sweden (SE) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.50 kW	2895 r/min	3.60 A	0.750	78.50 %	4.90 N·m	6.40
D	--	50 Hz	230 V	1.50 kW	2895 r/min	6.26 A	0.750	78.50 %	4.90 N·m	6.40
Y	--	50 Hz	415 V	1.50 kW	2905 r/min	4.00 A	0.670	77.20 %	4.90 N·m	6.40

Gross Weight	16 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 77.2 % Partial Load (75%) 74.6 % Partial Load (50%) 67.1 %
IM Class	IMV18 IM3611
IP Class	IP55
Insulation Class	ICLH
Invoice Description	M2AA 90S 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2

Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	13 kg
Product Type	2AA1__M2AA_IE1_AA
Quote Only	No
Replaced Product ID (OLD)	3GAA091001-NSA
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)