



PRODUCT-DETAILS

3GAA091002-CDEFT1

M2AA 90L 2

General Information

Product ID	3GAA091002-CDEFT1
ABB Type Designation	M2AA 90L 2
EAN	3GAA091002-CDEFT1
Catalog Description	M2AA 90L 2

Additional Information

ABB Type Designation	M2AA 90L 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Spain (ES) Sweden (SE) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EAN	3GAA091002-CDEFT1

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency
Y	--	50 Hz	690 V	2.20 kW	2890 r/min	2.50 A	0.840	0.00 %
Y	--	60 Hz	690 V	2.20 kW	3460 r/min	2.50 A	0.890	0.00 %

Gross Weight	16 kg
IC Class	IC411
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2AA 90L 2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	16 kg
Product Type	2AA1_M2AA_IE1_AA

Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)