



PRODUCT-DETAILS

# 3GAA091313-ASEEX1

## M3AA 090LB2

### General Information

Product ID	3GAA091313-ASEEX1
ABB Type Designation	M3AA 090LB2
Catalog Description	M3AA 090LB2

### Additional Information

ABB Type Designation	M3AA 090LB2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Spain (ES) Sweden (SE) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	2.20 kW	2870 r/min	4.40 A	0.860	84.60 %	7.30 N-m	6.90
D	--	50 Hz	230 V	2.20 kW	2870 r/min	7.65 A	0.860	84.60 %	7.30 N-m	6.90
Y	--	50 Hz	415 V	2.20 kW	2890 r/min	4.30 A	0.850	84.60 %	7.30 N-m	7.20

Gross Weight	21 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 84.6 % Partial Load (75%) 85.1 % Partial Load (50%) 84.1 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 090LB2
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2

Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	18 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)