

PRODUCT-DETAILS

3GAA091520-HFE

M3AA 90LB 2



General Information

Product ID	3GAA091520-HFE
ABB Type Designation	M3AA 90LB 2
Catalog Description	M3AA 90LB 2

Additional Information

ABB Type Designation	M3AA 90LB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	500 V	2.20 kW	2875 r/min	3.50 A	0.850	84.60 %	7.30 N·m	6.90
Y	--	60 Hz	575 V	2.20 kW	3480 r/min	3.00 A	0.850	85.80 %	6.00 N·m	7.90

Gross Weight	21 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 84.6 %

	Partial Load (75%) 85.7 % Partial Load (50%) 85.5 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 85.8 % Partial Load (75%) 85.9 % Partial Load (50%) 84.2 %
IM Class	IMB35 IM2001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 90LB 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GAA091520-AFE
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	18 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	F
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE2 High Efficiency Aluminum Motors
 Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



