

PRODUCT-DETAILS

3GAA102570-BSE

M3AA 100LG 4



General Information

Product ID	3GAA102570-BSE
ABB Type Designation	M3AA 100LG 4
Catalog Description	M3AA 100LG 4

Additional Information

ABB Type Designation	M3AA 100LG 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6306-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	4.00 kW	1415 r/min	9.10 A	0.760	83.20 %	26.90 N·m	5.50
D	--	50 Hz	230 V	4.00 kW	1415 r/min	15.80 A	0.760	83.20 %	26.90 N·m	5.50
Y	--	60 Hz	460 V	4.00 kW	1730 r/min	7.50 A	0.770	86.80 %	22.00 N·m	6.70

Gross Weight	30 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 83.2 % Partial Load (75%) 85.8 % Partial Load (50%) 85.5 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 86.8 % Partial Load (75%) 87.6 % Partial Load (50%) 86.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 100LG 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	25 kg
Product Type	3AA2_M3AA_IE2_AA
Quote Only	No
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors



