


PRODUCT-DETAILS

3GAA134001-ASECN

M3AA 132 incl. China energy label (+540)



General Information

Product ID	3GAA134001-ASECN
ABB Type Designation	M3AA 132S 8 +540
Catalog Description	M3AA 132 incl. China energy label (+540)

Additional Information

ABB Type Designation	M3AA 132S 8 +540
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	China (CN)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Torque	IS/IN
D	--	50 Hz	220 V	2.20 kW	710 r/min	10.70 A	0.690	29.30 N·m	3.40
Y	--	50 Hz	380 V	2.20 kW	710 r/min	6.20 A	0.690	29.30 N·m	3.40
D	--	50 Hz	230 V	2.20 kW	715 r/min	10.70 A	0.650	24.10 N·m	4.10

Gross Weight	47.38 kg
IC Class	IC411
IM Class	IMB3 IM1001

IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132 incl. China energy label (+540)
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	47.38 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

