


PRODUCT-DETAILS

# 3GAA134001-BSE

## M3AA 132S 8



### General Information

Product ID	3GAA134001-BSE
ABB Type Designation	M3AA 132S 8
Catalog Description	M3AA 132S 8

### Additional Information

ABB Type Designation	M3AA 132S 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Spain (ES) China (CN) Sweden (SE) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	230 V	2.20 kW	715 r/min	10.70 A	0.650	77.70 %	29.30 N·m	3.40
Y	--	50 Hz	400 V	2.20 kW	715 r/min	6.20 A	0.650	77.70 %	29.30 N·m	3.40
Y	--	60 Hz	460 V	2.20 kW	870 r/min	5.40 A	0.640	79.00 %	24.10 N·m	4.10

Gross Weight	47.38 kg
--------------	----------

IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3AA 132S 8
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	46 kg
Product Type	3AA2__M3AA_IE2_AA
Quote Only	No
Replacement Product ID (NEW)	3GAA134100-BSE
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

