


PRODUCT-DETAILS

3GBP092324-ADB

No Description Available



General Information

Product ID	3GBP092324-ADB
ABB Type Designation	M3BP 90SLC 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3BP 90SLC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Power Factor
D	--	50 Hz	400 V	1.10 kW	1430 r/min	0.780
Y	--	50 Hz	690 V	1.10 kW	1430 r/min	0.780
D	--	50 Hz	415 V	1.10 kW	1435 r/min	0.780

Gross Weight	27 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2

Full Load (100%) 83.7 %
 Partial Load (75%) 83.4 %
 Partial Load (50%) 81.2 %

IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	1 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	26 kg
Product Type	3BP2__M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Standards	IEC 60034-1
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

