


PRODUCT-DETAILS

# 3GBP284210-BSK

## M3BP 280SMA 8



### General Information

Product ID	3GBP284210-BSK
ABB Type Designation	M3BP 280SMA 8
Catalog Description	M3BP 280SMA 8

### Additional Information

ABB Type Designation	M3BP 280SMA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	37.00 kW	741 r/min	72.60 A	0.780	91.80 %	476.00 N-m	7.30
D	--	50 Hz	230 V	37.00 kW	741 r/min	126.00 A	0.780	91.80 %	476.00 N-m	7.30
Y	--	50 Hz	380 V	37.00 kW	740 r/min	76.00 A	0.810	91.80 %	476.00 N-m	6.80
D	--	50 Hz	220 V	37.00 kW	740 r/min	129.00 A	0.810	91.80 %	476.00 N-m	6.80
Y	--	50 Hz	415 V	37.00 kW	742 r/min	71.90 A	0.760	91.80 %	476.00 N-m	7.70
Y	--	60 Hz	460 V	37.00 kW	893 r/min	64.00 A	0.780	92.40 %	395.00 N-m	8.10

Gross Weight	625 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.8 % Partial Load (75%) 91.8 % Partial Load (50%) 90.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 92.4 % Partial Load (75%) 92.2 % Partial Load (50%) 90.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 280SMA 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	605 kg
Product Type	3BP3__M3BP_IE3_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE3 Premium Efficiency Cast Iron Motors

