

PRODUCT-DETAILS

3GBP289228-BDG

M3BP 280SMB 2-4



General Information

Product ID	3GBP289228-BDG
ABB Type Designation	M3BP 280SMB 2-4
Catalog Description	M3BP 280SMB 2-4

Additional Information

ABB Type Designation	M3BP 280SMB 2-4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
YY	--	50 Hz	400 V	90.00 kW	2965 r/min	153.00 A	0.910	93.00 %	290.00 N-m	7.30
D	--	50 Hz	400 V	65.00 kW	1488 r/min	117.00 A	0.850	94.40 %	417.00 N-m	8.60

Gross Weight	685 kg
--------------	--------

IC Class	IC411
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3BP 280SMB 2-4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Number of Poles (Low)	4
Output Power	90 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	665 kg
Product Type	3BP2_M3BP_IE2_CI
Quote Only	No
SCIP	54c45c7b-7581-40ab-b615-c1dcb277d8a7 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	Yes
Type of Duty	S1
UNSPSC	26101100 39120000
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

Motors and Generators → IEC Low Voltage AC Motors → Smoke Extraction Motors

