


PRODUCT-DETAILS

# 3GJM353420-BDG

## M3JM 355MLB 6



### General Information

Product ID	3GJM353420-BDG
ABB Type Designation	M3JM 355MLB 6
Catalog Description	M3JM 355MLB 6

### Additional Information

ABB Type Designation	M3JM 355MLB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	315.00 kW	992 r/min	330.00 A	0.830	95.70 %	3032.00 N·m	7.00
D	--	50 Hz	400 V	315.00 kW	992 r/min	570.00 A	0.830	95.70 %	3032.00 N·m	7.00
D	--	50 Hz	415 V	315.00 kW	993 r/min	549.00 A	0.830	95.70 %	3029.00 N·m	7.60

Gross Weight	2244 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.7 % Partial Load (75%) 95.7 % Partial Load (50%) 95.1 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 355MLB 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	2214 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Categories

---

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

