

PRODUCT-DETAILS

9MI34U4WNAB

30A,ILK,3P4W,DG,U2,480V,3PH,SC,NA



General Information

Extended Product Type	9MI34U4WNAB
Product ID	7TAA057980R0311
EAN	0708917313830
Catalog Description	30A,ILK,3P4W,DG,U2,480V,3PH,SC,NA
Long Description	DuraGard Rotary Controlled, Watertight, Non-Metallic Interlocked Receptacle- 30 Amp, 30 480V

Ordering

EAN	0708917313830
UPC	708917313830
Country of Origin	United States (US)
Customs Tariff Number	8537109170
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	10.25 in 260 mm
Package Level 1 Height	13.25 in 337 mm
Package Level 1 Depth / Length	14.88 in 378 mm

Additional Information

Application	For use where electrical connections need protection from water and/or dust entrance to the contacts or the wiring compartment.
Brand / Label	Russellstoll
Current Rating	30 A
Effective Date	20071112
Material	DuraV
Number of Batteries	0
Number of Conductors	4
Number of Poles	3
Product Name	ELECTRICAL BASE
Product Type	DuraGard Waterproof Connections
Special Functions	Not just "watertight"; Waterproof for washdown duty (DurORing Sealing) that eliminates the need for costly "weather boots" or "adapters."
Voltage Rating	480 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9MI34U4WNAB
Instructions and Manuals	9MI34U4WNAB

Classifications

ETIM 6	EC001322 - Round socket/plug for high currents
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors

