

PRODUCT-DETAILS

## **755LR-M0280** 35KV 600 ELBOW NO-SEALING KIT



General Information	
Extended Product Type	755LR-M0280
Product ID	7TAA060410R0008
EAN	0075114335102
Catalog Description	35KV 600 ELBOW NO-SEALING KIT
Long Description	600 Amp, 35kV, 600 Series Deadbreak Elbow (with Insulated Plug, Cap, Stud, Lug and Cable Adapter). Cable Insulation Diameter 1.370 inch to 1.630 inch. Universal Aluminum Compression Lug. Conductor Size AWG or kcmil Compressed Stranded 250, Solid 350.

Ordering		
EAN	0075114335102	
UPC	075114335102	
Country of Origin	United States (US)	
Customs Tariff Number	8535908020	
Selling Unit of Measure	each	

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	10.5 in	
	267 mm	
Package Level 1 Height	4.38 in	
	111 mm	
Package Level 1 Depth /	13.25 in	

## **Additional Information**

Application	Designed to provide Fully Shielded, Dead-Front Submersible Cable Connections to High-Voltage Apparatus.
Brand / Label	Elastimold
Color	Black
Current Rating	600 A
Effective Date	20170324
Environmental Conditions	Fully Submersible
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	35KV 600 ELBOW NO-SEALING KIT
Product Type	Deadbreak Elbow Connector
Size	Cable Insulation Diameter 1.370 inch to 1.630 inch.
Special Functions	100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Can be Easily Connected or Disconnected Using Standard Hand Tools and Equipment in a De-energized State. Optional Accessories allow Visible External Separation, By-Pass, Isolation, Dead-Ending, Grounding, and Testing as well as Adding Taps, Surge Arrestors, and Fault Current Indicators .
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	755LR-M0280	
Instructions and Manuals	755LR-M0280	

Classifications		
UNSPSC	39121421	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly	

## Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Installation}\ \mathsf{Products}\ \to \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{Cable}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{C$ 

## 337 mm

