

PRODUCT-DETAILS

755LRTP-L0280-DRG 35KV 600A STICK OP KIT DB



General Information	
Extended Product Type	755LRTP-L0280-DRG
Product ID	7TAA060440R0001
EAN	0075114205511
Catalog Description	35KV 600A STICK OP KIT DB
Long Description	600 Amp, 35kV, Stick-Op Connector Kit with Test Point, Insulated Cap and Reducing Tap Plug. Cable Insulation Diameter 1.180 inch to 1.465 inch. Aluminum Compression Lug. Conductor Size AWG or kcmil, Compressed Stranded 250 or Compacted Solid 300

0075114205511
075114205511
United States (US)
8535908020
each

Container Information		
Package Level 1 Units	1 piece	
Package Level 1 Width	13.25 in	
	337 mm	
Package Level 1 Height	10.5 in	
	267 mm	
Package Level 1 Depth /	4.37 in	

Length 111 mm

Application	Mates with a 600 Amp elbow interface and provides a 200 Amp load break
	tap, an access hole thru the bore of the reducing tap plug allows use of a
	600AT operating tool to bolt and secure the component to a mating 600
	Amp elbow and apparatus bushing.
Brand / Label	Elastimold
Color	Black
Current Rating	600 to 200 A
Effective Date	20141118
Environmental	Fully Submersible
Conditions	
Includes	Elbow Housing, Reducing Tap Plug, Insulated Cap, Cable Size Adapter,
	Compression Lug, Lubricant, Instruction Sheet, Crimp Chart.
Insulation Material	Yes, EPDM Rubber
Material	Housing - EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Stick-OP Elbow Connector
Size	Cable Insulation Diameter 1.180 inch to 1.465 inch.
Special Functions	Test Point. 35kV Reducing Tap Plug. Includes Hex-Broach for Torque
	Installation. Peroxide-Cured Insulation and Jacket.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C
Voltage Rating	35 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	755LRTP-L0280-DRG
Instructions and	755LRTP-L0280-DRG
Manuals	

Classifications

39121421
Product Not in WEEE Scope
4586 >> Electrical connector assembly

Categories

755LRTP-L0280-DRG 3

