

1 piece

PRODUCT-DETAILS

## **750GP** 35KV 600A DEADBRK INSUL PLUG 2.29FT



General Information		
Extended Product Type	750GP	
Product ID	7TAA122040R0004	
EAN	0783786647460	
Catalog Description	35KV 600A DEADBRK INSUL PLUG 2.29FT	
Long Description	35kV 600 Amp Series Deadbreak Grounding Plug (2.29 Foot (27.48 inch) 1/0 AWG Grounding Cable)	

Ordering		
EAN	0783786647460	
UPC	783786647460	
Country of Origin	United States (US)	
Customs Tariff Number	8535908020	
Selling Unit of Measure	each	

## **Container Information**

Package Level 1 Units

Additional Information	
Application	Grounding plug is inserted into a parking stand with an insulated hot stick
	and secured in place.

Brand / Label	Elastimold
Effective Date	19980108
Material	Stainless Steel Mounting Bracket, EPDM Rubber Plug.
Number of Batteries	0
Product Name	"electrical connector,>1000v"
Product Type	Grounding Plug
Size	(Ground Lead 1/0 AWG x 27.48 inches, 2.29 foot, 697.99 mm). Plug has 3 inch (76.2 mm) Diameter and is 5.00 inches long (127.0 mm). Center of Plug to Top of Eye Hook is 4.12 inches (104.7 mm).
Special Functions	Fully Rated 35kV, 600 Amps Deadbreak Grounding Plug. Allows visible external separation and grounding. Stainless Steel Bracket. Hot Stick Operable. 2.29 Foot (27.48 inch or 697.99 mm) 1/0 AWG Grounding Cable
Standards	ANSI/IEEE Standard 386

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	750GP	
Instructions and Manuals	750GP	
Classifications		
UNSPSC	26121630	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories	

## Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Installation}\ \mathsf{Products}\ \to \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{and}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \mathsf{Accessories}\ \mathsf{Apparatus}\ \to\ \mathsf{Cable}\ \to\ \mathsf{Apparatus}\ \to\ \mathsf{Apparatus$ 

